

SMS Coverall



SPECIFICATIONS	
Code	295
Description	SMS Coverall
Features and Benefits	Certified for asbestos removal and hazardous substances handling Strong tear-resistant material Comfortable to wear Zip at the front and extra neck protection Hooded with elasticated wrists and ankles
Areas of Use	Trade Cleaning Medical Emergency Services
Colour	White
Sizes Available	S / M / L / XL / XXL / 3XL / 4XL 25 / Carton

PHYSICAL PROPERTIES	
Raw Material	SMS
Normal Weight (gsm)	55

The figures above are based off average results from multiple tests, results may vary + or - 5%

PGL, as the distributor of Selfgard™ Disposable Products in New Zealand hereby certifies that the following product complies with **FDA 510(k)**, for use in food and medical activities except surgery and are manufactured and processed under recognised food safety standards.



QUALITY STANDARDS

- EN ISO 13688 : 2013, EN ISO 13982-1 : 2004 TYPE 5, EN 13034 : 2005 TYPE 6
EN 1073-2 : 2002 CLASS 1, EN 1149-5 : 2018, EN 14325 : 2004
- (EU) 2016/425
- Type 5: Barrier to air born particulate materials & Dust
- EN ISO 13982-1 Types 5: Protection against airborne solid particulates
- EN 13034 Type 6: Limited protective performance against light spray, liquid aerosol or low pressure, low volume splashes
- EN 1073-2 Class 1: Total Inward Leakage
- Certified to the following Personal Protective Equipment model: Category 3

HAZARD IDENTIFICATION

Eye Contact	Negligible hazard.
Skin Contact	Negligible at -18°C to +38°C. Exposure to hot materials may cause burns.
Inhalation	Negligible at -18°C to +38°C. Vapours may form at elevated temperatures to which may irritate eyes and respiratory tract.
Ingestion	Harmful if swallowed.

FIRST AID MEASURES

Eye Contact	This is an inert solid. Remove like any other foreign object in eye.
Skin Contact	Remove item if an allergic reaction occurs. Wash exposed area with soap and water. If symptoms persist seek medical attention.
Inhalation	In case of exposure to melting vapours remove victim to place of fresh air.
Ingestion	If swallowed induce vomiting immediately after giving two glasses of water.

PRECAUTIONS OF USE

Exposure Standards	None, this product can be worn continuously.
Personal Protection	No requirement.
Flammability	Flash point 400°C (includes auto ignition).
General Hazard	Materials to avoid are acids or any harsh chemical which may cause deterioration of the glove.

SAFE HANDLING INFORMATION

Storage	Store in a dry cool temperature away from direct sources of heat or light.
Transport	No special requirements.
Spills and Disposal	Product is non-hazardous and non-toxic.

OTHER INFORMATION

To prolong product life, the item should be stored in a cool, dry location, located away from sources of heat and light.

Selfgard™ products are registered and under trademark of PGL and sold exclusively through selected distributors. For further information on Selfgard™ please email sales@pgl.co.nz, phone 0800 766 662 or contact your distributor.